

COMPARATIVE TABLE

		Klick Light	Klick Electric	Klick Scrambler	Klick Power	Klick Race	Klick Power Plus	Klick Monster
General	Motor	Brushless 750W with epicyclic reducer	Brushless 750W with epicyclic reducer	Brushless 750W/HP (Hight Performance)	Brushless 750W with epicyclic reducer	Brushless 1500W	Brushless 750W/HP (Hight Performance)	Brushless 1500W
	Torque	45Nm	50Nm	65Nm	50Nm	50Nm	60Nm	50Nm
	Weight *(3)	8,8 kg	10,2 Kg	11,8 Kg	10,4 Kg	13,2 Kg	10,6 Kg	15,3 Kg
	Materials: Frame / Fork / Wheel Rim	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminum/Steel/Aluminum
	Wheel Diameter *(5)	12 Inch / 312mm	14 Inch / 363mm	13,3 Inch / 340mm	14 Inch / 363mm	14 Inch / 363 mm	16 Inch / 408mm	20 Inch / 560mm
Battery	Lithium-ion battery with automatic Over Voltage protection*(1)	48V x 11,6 Ah, 528 Wh, Weight 3,1 Kg. Autonomy 45/50km						
	Lithium-ion battery with automatic Over Voltage protection*(1)	48V x 5,8 Ah, 280 Wh, Weight 2,0 Kg Autonomy 20/25 Km						
	Lithium-ion battery with automatic Over Voltage protection*(1)	48V x 2,9 Ah, 140 Wh, Weight 1,4 Kg Autonomy 14/12 /Km						
Tyre	Standard tyre	Allroad 12 (L55mm)	Allroad 14/2.125 (L55mm)	Allroad 300/8 (L80mm)	Allroad 14/2.50 (L60mm)	Allroad 14/2.50 (L60mm)	Allroad 16/2.125 L.60mm)	Off Road 20/40 (L95mm)
	Tyre optional		Allroad 14/2.50 (L60mm)	Motard 300/8 (L80mm)	Enduro 14/2.125 (L55mm)	Enduro 14/2.125 (L55mm)		
	Tyre optional		Enduro 14/2.125 (L55mm)		Cross 2.5x10*(2) (L63mm)	Cross 2.5x10*(2) (L63mm)		
	Tyre optional		Cross 2.5x10*(2) (L63mm)		Allroad 14/2.125 (L55mm)	Allroad 14/2.125 (L55mm)		
Brake	Disc brake with mechanical caliper	Standard single brake caliper	Standard:double caliper	Standard:double caliper	Standard:double caliper	Standard:double caliper	Standard:double caliper	Standard:double caliper
	Disc brake with double piston hydraulic caliper	Optional	Optional	Optional	Optional	Not installable	Optional	Not installable
Driver assistance	Electronics by Klaxon with certified software according to IEC62304	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Maximum speed in accordance with the law *(4)	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp	20Km/h - 12,4Mmp
	5 speed levels selectable via the push-button panel	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Reverse gear with speed customizable from the Display	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Adjustable acceleration from the display	Standard/10 levels	Standard/10 levels	Standard/10 levels	Standard/10 levels	Standard/10 levels	Standard/10 levels	Standard/10 levels
	ISC (Intelligent Speed Control)	Standard	Unavailable	Standard	Standard	Standard	Standard	Standard
	EBS (Electronic Brake System) can be activated via brake levers & buttons	Standard	Unavailable	Standard	Standard	Standard	Standard	Standard
	MDC (Motion Direct Control)	Standard	Unavailable	Standard	Standard	Standard	Standard	Standard
	HCC (Hill Holder control) Hill start assist and automatic parking.	Optional	Unavailable	Optional	Optional	Optional	Optional	Optional
	Electronic brake with regeneration	Standard	Unavailable	Standard	Standard	Standard	Standard	Standard
	Electronic braking intensity adjustable from the display	ON/OFF + 9 levels	Unavailable	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels
	Automatic electronic brake when the accelerator is released	ON/OFF + 9 levels	Unavailable	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels	ON/OFF + 9 levels
Various	Max speed adjustable from the display	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	High visibility color LCD display	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	USB socket for Smartphone charging positioned on the push-button panel	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Automatic headlight switching on with night/day function. (Light optional)	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off
	Reversing activation warning sound	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off	Standard/can be switched off
	Battery Size Management. Can be set from the display according to the battery used.	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Attachment to the wheelchair with assisted lifting	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Self-adjusting, removable stand	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Steering hardness adjustment for anti-rotation when parked	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Certification approved by TÜV EN12184 - CE - FDA	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Medical device software certification according to IEC62304	Yes	Yes	Yes	Yes	Yes	Yes	Yes

*(1) The range depends on the type of battery installed. The indicated values refer to tests conducted on flat ground at a speed of 10 km/h with a user weight of 75 kg.

*(2) The Cross tyre is recommended only for off-road use.

*(3) The indicated weight refers to the Klick without the battery.

*(4) The indicated speed is the maximum speed of the device, but please check the legal limits in the country of use.

*(5) The wheel diameter in mm may vary depending on the installed tyre brand.